

BT8001 SPECIFICATIONS

box acrylic freestanding bathtub

FEATURES:

- Freestanding or alcove acrylic bathtub
- Alcove installation requires separate tile flange, not included.
(Blu recommends TF.BTSB tile flange)
- Streamlined, high profile one piece design
- 60" (1524mm) L x 32" (813mm) W x 21" (533mm) H
- Suitable for left or right hand drain installation
- Includes polished chrome waste and slot overflow
- Tailpiece not included. (Blu recommends BTWaste.RN)

SPECIFICATIONS:

Basin Area:	45 1/4" (1146mm) x 26" (660mm)*
Top Area:	52" (1320mm) x 28" (711mm)*
To Overflow:	2 1/4" (60mm)*
Water Depth:	14 1/2" (371mm)*
Capacity:	68GL (258L)
Slope of Backrest:	74°
Weight:	73lbs (33kg)
Hot water supply req'd:	Should be 70% of water capacity of tub or greater
Warranty:	Five Year Warranty (Residential use) One Year Warranty (Commercial use)
Material:	Acrylic
Shipping Weight:	43kg
Shipping Dimensions:	(LWH) 62 1/2" x 32" x 22" (1585mm x 835mm x 565mm)

COLORS / FINISHES:

- White gloss
- Optional brushed nickel waste & slot overflow available

ACCESSORIES:

- Recommend TF.BTSB tile flange for alcove installation
- Recommend BTWaste.RN Island tub drain for easy installation

INSTALLATION NOTES:

Install this product according to the installation guide.
Floor support under bath must provide for a minimum of 1400 lbs (635kg). Installation will vary. Our products must be installed by certified professionals only and according to our installation guide as well as federal, provincial / state and local building codes and regulations

CODES / STANDARDS APPLICABLE:

- Meets or exceeds ANSI / ASME standard
Z124.1.2 and CAN / CSA B 45 requirements
- IAPMO / UPC / cUPC



*Approximate measurements for comparison only.
Note: These dimensions and specifications are subject to change without notice.

